

Veritas R8Plus

THE PROFESSIONALS' CHOICE



**NOW ACCEPTS THE VERITAS EXCEL LCD REMOTE KEYPAD
USE AS AN EXTRA KEYPAD OR AS AN ENGINEER'S PROGRAMMER**

Already renowned for its reliability, the *Veritas R8 Plus* has been upgraded with a host of new features. Installation and servicing are now even quicker. Operation is easier and more intuitive. Programming has been both simplified and extended. Make the right choice - the *Veritas R8 Plus*.

Outstanding features include:

- ✓ 8 FULLY PROGRAMMABLE ZONES PLUS TAMPERS
- ✓ 8 CHANNEL COMMUNICATOR INTERFACE WITH LINE MONITOR
- ✓ 4 PROGRAMMABLE PART SET SUITES
- ✓ 8 PROGRAMMABLE ACCESS CODES
- ✓ 250 EVENT LOG (TIME/DATE STAMPED)
- ✓ UPLOAD/DOWNLOAD COMPATIBLE
- ✓ EOL OR NORMALLY CLOSED ZONE OPERATION
- ✓ ACCEPTS UP TO 6 REMOTE KEYPADS (LED OR LCD)
- ✓ EN 50131 GRADE 2
- ✓ 1.2mm STEEL ENCLOSURE ALSO AVAILABLE

Ask your distributor today for the new **Texecom** full colour Product Guide.

Texecom
www.texe.com

VERITAS R8 PLUS FEATURES



Touchtone Backlit Keys

8 Fully Programmable Zones Plus Tamper

The *Veritas R8 Plus* features 8 fully programmable zones plus an additional global system tamper. Each zone operates in either EOL or single pole mode and can be programmed to any of 8 different zone types ensuring exceptional system flexibility.

8 Channel Communicator Interface with Line Monitor

With an on-board 8 channel communicator interface, the *Veritas R8 Plus* can be used in conjunction with other signalling equipment as part of an ACPO compliant monitored alarm.

Universal Programming Platform

The *Veritas R8 Plus* utilises the same intuitive programming platform as the rest of the *Veritas Series*, ensuring instant product familiarity across the range.

European Standards

PD 6662 and EN 50131 Grade 2 Environmental Class II.
Conforms to European Union (EU) Low Voltage Directive (LVD) 73/23/EEC (amended by 93/68/EEC) and Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC). The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.



Discreet Aesthetics



Compatible with *Veritas LCD Keypad*

Veritas R8 Endstation

Current Consumption:	Quiescent current:	<50mA
	Alarm current:	<150mA
Power Supply:	Mains Supply Voltage Rating:	230VAc/115VAc ($\pm 10\%$)
	Max. Total Current Rating:	1Adc at 230VAc/115VAc ($\pm 5\%$)
	Ripple:	<5%
Dimensions:	282mm x 225mm x 80mm	



Hinged PCB Chassis



Remote Endstation

Veritas LED Remote Keypad

Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	140mm x 105mm x 35mm	

Veritas LCD Remote Keypad

Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	146mm x 116mm x 30mm	



Slim, Low Profile Design

VERITAS SERIES



Veritas 8

Best selling stand alone control panel. Features 8 fully programmable zones & accepts up to 6 backlit remote keypads. Utilises the same intuitive programming platform as the rest of the *Veritas Series*.



Veritas 8 Compact

Slimline discreet stand alone control panel. Features 8 fully programmable zones & accepts up to 6 backlit remote keypads. Nominated Product of the Year 2000 by PSI magazine.



Veritas R8/R8 Plus

Best selling control panels with remote keypad. Featuring 8 fully programmable zones & accept up to 6 backlit remote keypads. *Veritas R8 Plus* includes EOL wiring, communicator interface & accepts *Veritas Excel LCD* keypads.



Veritas Excel

All the features of the *Veritas R8 Plus* including an *LCD* keypad for even easier programming & operation. Banner text, user & zone names are all programmable & the 250 event log can be accessed directly.

Texcom products are protected by UK and international patents, trademarks and registered design rights. Registered Design No. 1573433, 2041830, 2047440, 2055230 & 2089016.

© 1995 - 2005 Texcom Limited.



Certificate Number: FM 35285



VRB + . EU6